

STANDARD TOWING HEADS


THE STANDARD TOWING HEAD

The standard towing head is a simple device that attaches to the end of a piece of pipe to allow it to be pulled. It is designed for use with polyethylene pipe of wall thickness between *SDR11 and SDR 17.6.

(Other materials and wall thicknesses can also be accommodated upon request.)

It is operated by simply inserting it into the pipe and turning the eyebolt. The turning action draws a cone into four toothed segments which are forced into the wall of the pipe. The harder the eye is pulled the harder the pipe is gripped. The grip is so good that it is possible to stretch the pipe!

*Standard diameter to wall thickness ratio



EYEBOLTS

The eyebolt is the critical component. Brewis towing heads are fitted with a specially forged, single piece, high tensile steel, eyebolt. This has superior strength when compared with a welded eyebolt used by other manufacturers. Why take the risk with inferior copies?



BENEFITS


The standard towing head provides a quick, simple and highly effective way to attach a pulling eye to a pipe.

- Installed and removed in seconds.
- The harder the eye is pulled the harder the pipe is gripped.
- Proven tooth profile for maximum grip.
- Huge range of sizes from 20mm to 900mm. (including IPS imperial sizes)
- Metric sizes cover SDR11 to 17.6 on sizes up to 355mm.
- Single piece, high tensile steel, drop forged eyebolts.
- Designed in 1984 by Rod Brewis and used all over the world.

AUSTRALIA
03 9068 5688
 +61 3 9068 5688
 sales@blick.group
 www.blick.group

NEW ZEALAND
07 849 2366
 +64 7 849 2366
 sales@blick.group
 www.blick.group





Pipe Size	Min. Grip	Max. Grip	Eyebolt Thread	L	d	t	Weight
Stock sizes	mm	mm					Kg (approx)
25	19	24	M6	31	16	5	0.15
32	24	28.5	M8	30	14	8	0.24
40	30	37	3/8" BSW	43	18.5	9	0.42
50	39	46	1/2" BSW	60	29.5	11	0.98
55	42	49	1/2" BSW	60	29.5	11	1.20
63	48	58	1/2" BSW	60	29.5	11	1.66
75	57	70	1/2" BSW	60	29.5	11	2.46
90	70	82	3/4" BSW	84	38	19	3.90
100	77	93	3/4" BSW	84	38	19	4.80
110	86	99	3/4" BSW	84	38	19	6.25
125	97	111	3/4" BSW	87	38	19	5.60
140	108	130	3/4" BSW	87	38	19	8.60
160	124	148	1" BSW	100	43	22	11.6
180	141	163	1" BSW	100	43	22	15.0
200	157	182	1" BSW	100	43	22	19.0
225	175	201	1" BSW	100	43	22	22.5
250	196	225	1" BSW	100	43	22	31.5
280	220	252	1" BSW	100	43	22	32.5
315	249	282	1 1/2" BSW	155	74	30	43.0
355	280	315	1 1/2" BSW	155	74	30	53.0
400-11	315	335	1 1/2" BSW	155	74	30	62.0
400-17.6	345	358	1 1/2" BSW	155	74	30	72.0
450-11	353	375	1 1/2" BSW	160	74	30	82.0
450-17.6	384	405	1 1/2" BSW	160	74	30	90.0
500-11	395	415	1 1/2" BSW	160	74	30	94.0
500-17.6	432	446	1 1/2" BSW	160	74	30	110.0

Full range of IPS sizes also available.

Need some shackles with your pullers?



Brewis reserves the right to amend the specifications without notice. E&OE.

AUSTRALIA
03 9068 5688
 +61 3 9068 5688
 sales@blick.group
 www.blick.group

NEW ZEALAND
07 849 2366
 +64 7 849 2366
 sales@blick.group
 www.blick.group

